SUPERTOUCH®



F

Colourways:



Black/Green

PRODUCT INFORMATION

DEFLECTOR F

Description:

With a textured palm combined with high performance our maximum cut level Deflector F glove offers enhanced cut resistance making them the perfect choice for a large range of tasks with maximum protection.

- ✓ Conforms to EN 388:2016 levels 4-5-4-4-F
- ✓ Highest ISO Cut Level F
- ✓ Highest level of abrasion, tear & puncture.
- ✓ Extended ribbed cuff length
- ✓ Seamless liner

Type:

Black Sandy Nitrile Coating
Liner - HPPE/Steel/Fiber/Polyester/Spandex

Applications:

Tasks with general handling, disposal operations, baggage handling, construction, maintenance, gardening and sharp handling.

Product Codes:

|--|

Standards:




EN 388 2016



Abrasion: 4
Blade Cut: 5
Tear: 4
Puncture: 4
ISO Cut: F

PPE Regulation (EU) 2016/425

BS EN 420:2003+A1:2009 - Sizing & Dexterity: PASS BS EN 388:2016 - Protection Against Mechanical Hazards



Size Chart:

Measurements in mm	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)
Hand Length (A)	171	182	192	204	215
Hand Circumference (B)	178	203	229	254	279

Issue No.:3 Issue Date: 21/06/2019



Packaging: 1 pair per bag - 12 bags per master bag - 10 master bags per case

Outer Carton Artwork:



The information shown on this specification sheet is intended as a guide and is advisory only. All details were correct at the time of issue. As conditions of use are ultimately beyond our control, we advise that the product is tested for the particular application before use.