

78273 - 45CM
78373 - 60CM

PROCHEM ULTRA GLOVES

ABOUT THIS PRODUCT

Our Prochem[®] Ultra unlined natural rubber gloves provide exceptional chemical resistance, making them ideal for chemical handling and industrial cleaning tasks. Available in two lengths, these gloves ensure you have the right level of protection for various tasks, including general wet handling and industrial cleaning.

EN 388:2016+A1:2018

| Test | Performance Level Achieved | Maximum Performance Level |
|---------------------|----------------------------|---------------------------|
| Abrasion Resistance | 4 | (4) |
| Cut Resistance | 1 | (5) |
| Tear Resistance | 2 | (4) |
| Puncture Resistance | 1 | (4) |
| ISO Cut level | X | (F) |

EN ISO 374-1:2016+A1:2018

| Chemical | Permeation Levels | Degradation |
|--------------------------|-------------------|-------------|
| A Methanol | 6 | 0.4% |
| K Sodium hydroxide 40% | 6 | -10.2% |
| L Sulphur acid 96% | 4 | 31.4% |
| M Nitric acid 65% | 6 | 16.2% |
| N Acetic acid 99% | 5 | 20.0% |
| O Ammonium Hydroxide 25% | 3 | -8.1% |
| P Hydrogen Peroxide 30% | 6 | 32.1% |
| T Formaldehyde | 6 | -4.4% |

EN 407:2020 Protective gloves against thermal risks [Heat and/or fire]

| Test | Performance Level Achieved | Maximum Performance Level |
|----------------------------------|----------------------------|---------------------------|
| Limited flame spread | X | 4 |
| Contact heat | 1 | 4 |
| Convective heat | X | 4 |
| Radiant heat | X | 4 |
| Small splashes of molten metal | X | 4 |
| Large quantities of molten metal | X | 4 |

This product does not have flame protection and should not come into contact with a naked flame.

CERTIFICATION



MATERIALS

Unlined rubber gloves.

STORAGE

Keep in cool dry place away from direct.

PACKAGING

1 Pair per bag - 24 pairs per carton.



CONTAINS LATEX

Black

S/7-2XL/11

78273 - 45CM
78373 - 60CM

- Achieves type A chemical protection for EN374-1
- Highest Abrasion level for EN388
- Protection against bacteria and viruses conforming to EN374-5
- New Rubber formulation for a softer feel
- Heat resistance to 125degrees for EN407
- Frictionless design for easy on and off use
- Available in two lengths for arm protection
- Feature rolled beaded cuff
- CAT III