



ES9920ST

**Cappture™** ANSI • CE • CSA •



DIELECTRIC

Dielectric // Fits over prescription glasses // Temples extend from browbar to avoid interference with prescription frame's temples // Rubber gasket option is available



**Lens and Temples | 2 Variations**

- ES9910ST ••• Clear **H2X** AF
- ES9920ST ••• Grey **H2X** AF

**Rubber Gasket | 1 Variation**

- ES9910STMGRG ••• Clear **H2MAX** AF

**WATCH THE VIDEO**

Vimeo.com/Pyramex/H2MAX



**There's more to see at  
PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

ANSI Z87.1+ standards [•] | European EN166 [•]

Canadian CSA Z94.3-15 & [•] third-party certification [•]

For specific lens options visit our website or contact your sales representative.

06/17

## Cappture™

### General Specifications

Weight: 29.5 gm | 51.7 gm with rubber gasket  
 Bridge: 23.1 mm  
 Lens base: 2.5 curve  
 Lens size diagonal: 145.7 mm  
 Lens size vertical: 51.5 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 160 mm  
 Overall width (hinge - hinge): 132.5mm  
 Closest point between temple tips: 88 mm

### Materials

Lens: polycarbonate  
 Nosepiece: polycarbonate  
 Temple: polycarbonate  
 Hinge: nylon + polycarbonate  
 Rubber gasket: polycarbonate and thermoplastic rubber (TPR)

Part No.	Lens Marking	Temple Marking
ES9910ST	2C-1.2 P 1FT CE	CE P EN166 FT
ES9920ST	5-2.5 P 1FT CE	CE P EN166 FT
ES9910STMARG	2C-1.2 P 1FT KN CE	CE P EN166 FT

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Colour Perception

C: Unimpaired colour perception

#### Protection Class

1.2 - 6: Degree of visible light filtration

#### Optical Class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s  
 T: Impact protection at extreme temperature conditions

#### Symbols

P: Manufacturer's mark  
 K: Resistance to surface damage by fine particles  
 N: Filter with anti-fog  
 CE: Europe standard

### Temple Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact  
 T: Impact protection at extreme temperature conditions



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com