



PYRAMEX
Perform At Your Peak

Fyxate™ ANSI CE



DIELECTRIC



FOAM
PADDING



RUBBER
NOSEPIECE



RUBBER
TIPS



INCLUDES
STRAP

Dielectric

Rubber temple tips and nosepiece

Single wraparound lens

Foam padding available on select options

Quick release strap available on foam padded options only

Part No.	Lime Temple Tips
ESGL10210S ●●	Clear
ESGL10210ST ●●	AF Clear H2X
ESGLS10220S ●●	Gray
ESGL10220ST ●●	AF Gray H2X
ESGL10280S ●●	I/O Mirror
Part No.	Foam Padded
ESGL10210STMFP ●●	AF Clear H2MAX
ESGL10220STMFP ●●	AF Gray H2MAX



vimeo.com/pyramex/h2max



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ (●) and European EN166 (●) standards. All lenses are hard coated polycarbonate scratch-resistant and provides 99% protection from harmful UV rays.



PYRAMEX
Perform At Your Peak

Fyxate™

General Specifications

Weight: 23.2 gm and 46.35 gm (with foam)
 Bridge: 12.8 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.5 mm
 Lens size vertical: 42.72 mm
 Lens thickness: 1.95 mm
 Overall length (lens - tip): 160.8 mm
 Overall width (hinge - hinge): 129 mm
 Closest point between temple tips: 73 mm

Materials

Lens: polycarbonate
 Nosepiece: thermoplastic rubber (TPR)
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Foam gasket: nylon and ethylene-vinyl acetate (EVA)
 Strap: polyester

Part No.	Lens Marking	Temple Marking
ESGL10210S	2 C - 1.2 P 1 F CE	CE P EN166 F
ESGL10210ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESGLS10220S	5 -2.5 P 1 F CE	CE P EN166 F
ESGL10220ST	5 -2.5 P 1 F N CE	CE P EN166 F
ESGL10280S	5 -1.7 P 1 F CE	CE P EN166 F
ESGL10210STMFP	2 C - 1.2 P 1 F K N CE	CE P EN166 F
ESGL10220STMFP	5 -2.5 P 1 F K N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Colour perception

C: Unimpaired colour perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967